



GEHL Maintenance Chart

Service Procedure	Maximum Interval		
	10 Hours (or daily)	250 Hours	500 Hours (or Annually)
Foreign Material Removal	L		
Check Engine Air Cleaner Restriction Indicator	L		
Check Engine Oil Level	L		
Check Hydraulic Oil Level	L		
Check Tire Pressures	L		
Grease Lift Arm, Hitch, Cylinder Pivots and Latch Pins	L		
Check Bucket Cutting Edge	L		
Test Safety Interlock System	L		
Check Coolant Level	L		
Clean Cooling System	L		
Check Drive Chain Tension		L	
Check Wheel Nuts Torque	M	L	
Check All-Tach Pivot Torque		L	
Check Oil Level in Chaincases		L	
Check Alternator/Fan Belt Tensions		L	
Change Engine Oil and Filter	O	V	L
Change Hydraulic Oil Filter	O		L
Check Battery			L
Check Engine Mounting Hardware			L
Change Fuel Filters			L
Change Hydraulic Oil			U
Change Chaincase Oil	O		U

- M Perform the initial procedure at 2 hours then at "L" intervals
- O Perform the initial procedure at 50 hours then at the "U" intervals
- V Severe operating conditions
- U Perform the procedure at 1000 hours